

WE GLAD TO INTRODUCE COMPANY WE BUILD THROUGH THE YEAR WITH PROFESSIONALISM

ABOUT THE COMPANY

execal

A Css Creation co.

CSS Creation was established in 2013 for sales and service support of stretch ceiling solutions, having its own Brand "LEXECAL Stretchceiling".

To remain competitive and meet customer's expectations we lay great emphasis on continuous up gradation of products and related technologies.

We are committed for the advancement of technologies in the development of customized

products and flawless operations. Our determination is to provide quality products and reliable customer services to our customers with innovative and cost effective method.

We have inhouse team of 18+ Trained and Skilled employees. Working in different locations. We undertake turnkey projects.

OUR CORE VALUES

To earn affection of Customers by delivering to their experience and value.

Ensuring highest quality of deliverables and standards. Delivering latest in cutting edge Technology to customers at an affordable price.

OUR VISION

Our vision is to be globally admired organization that enhances our products & services with our highly skilled and motivated professional team by getting support of community to serve the Industry and adding value in development of the India.

ADVANTAGES



Lexecal Stretch Ceiling is 100% Recyclable.

Adry working site with no smell or dust.

No painting required, with minimum maintenance. Easily washable with water or any particular cleaning solutions.

Can be easily installed and dismantled, without any damage to the material thus improving accessibility.

Perfect for humid Environments.



Registration in terms of reaction to fire in public place B-S2 do (Formerly M1, B1, Assessed to class O)

No emission of CFC or HCFC.

Lexecal Stretch Ceiling are produced with plasticisers guaranteed with no phtalate.



Light Reflection : For Translucent Ceiling, 10% Light.

Light Transmitting: For Translucent 75% approx.

Physical Properties: Thickness 0.170 mm

Weight 221 gms/m2



Ecological: 100% Recyclables

Acoustic: Sound Absorption Average: 0.85,

Noise Reduction Coefficient: 0.85

Fire Safety: Fire Behaviour B, Smoke Production S2

Flaming Droplets d0, Fire Classification

B-s2, d0



TECHNICAL INFORMATION FOR TYPICAL STRETCH CEILINGS

Maximum Recommended Square Metre Size Per Sheet on Aluminium Tracks

Matt – 60 sq. m / Satin – 60 sq m / Lacquer & Metallic – 60 sq. m / Translucent – 50 sq. m

Weight per sq mt

Matt - 0.18kg / Satin - 0.17kg / Lacquer & Metallic 0.17kg

Acoustic Properties DIN EN 20354 (ISO 354) - 100mm VOID

Absorption coefficients guide for typical installation using stretched materials with minimum 45mm insulation above.

Standard Non Perforated

| Frequency (HZ) | 100 | 125 | 250 | 500 | 1k | 2k | 4k |
|---------------------------|------|------|------|------|------|------|------|
| Absorption Coefficient () | 0.14 | 0.17 | 0.63 | 0.64 | 0.24 | 0.19 | 0.14 |

Perforated 500,000 holes / per sq mt

| Frequency (HZ) | 100 | 125 | 250 | 500 | 1k | 2k | 4k |
|---------------------------|------|------|------|------|------|------|------|
| Absorption Coefficient () | 0.15 | 0.18 | 0.68 | 1.01 | 0.79 | 0.70 | 0.61 |

Thermal Emission Factor NH/PTH

Matt - 0.16 / Satin 0.16 / Lacquer & Metallic - 0.15

Thermal Emission Factor ESPIL

Matt 0.84 / Satin 0.84 / Lacquer & Metallic - 0.85

Antistatic

Typical average for Lacquer – 4.10 at 11ohms

Light reflectance and transmission

| =:g::::::::::::::::::::::::::::::::::: | | | | | |
|--|---------------|--------------|--|--|--|
| Colour / finish | Reflectance % | Transmission | | | |
| White | Lacquer | 78.8 9.6 | | | |
| White | Matt | 81 9.8 | | | |
| Translucent | 39.2 | 74.9 | | | |









Fire Rating

Awarded new Euro classification to: EN13501-1, Rating: B S1 d0, UK Equivalent to Class "0" designation for building regulations.

Vapour Barrier

Stretch has gained awards from the Swimming Pool and Allied Trades Association – Vapour Tested NF EN 14716 § 4.1.3

Hygiene Typical Microbiological Trial

14 Days – chlorinated solution wipe after 7 days – inoculated Bacterium – E.Coli, Listeria, Salmonella, Yeast, Mould – NONE DETECTED.

General

1Ceiling sheet thickness nominal 0.2mm and is manufactured in roll from with ultrasonic flush welded joints starting at approx 1.5m centres. Plastic track can be heat bent to match curved.

A Css Creation co.

SCOPE OF STRETCH CEILING



































GLOSS 500 CM MAT 500 CM M 303 G 225 G 303 **MATTE 320 CM** G 305 G 307 G 347 G 501 MT 007-303 G 507 MT 010-303 G 511 MT 010 Gold G 571 **SHELLS 320 CM SATIN 320 CM** S 303 **PL-SH 303** SH 303 SH 307 SH 501 SH 507



SP 303

LEAVES 320 CM BROCADE 320 CM GALAXY 320 CM LV 303 PL-3D 303 GL 162 LV 307 3D 303 3D 501 LV 501 **GL 108** 3D 347 LV 507 GL 303 **MOSAIC 320 CM METALLIC 320 CM** GL 347 GL 462 **PL-MS 303** ST 81 **EXCLUSIVE 320 CM** MS 303 ST 87 MS 501 M 904 **SPRING 320 CM CLOTH 310, 350** 410, 450, 505 CM Water **Thread PL-SP 303**

00950450

Clouds







GLOSS 320 CM GLOSS 320 CM G 100 G 400 G 110 G 402 G 404 G 114 G 406 G 120 G 408 G 156 G 412 G 160 G 424 G 201 G 442 G 223 G 462 G 225 G 476 G 227 G 478 G 229 G 490 G 235 G 501 G 507 G 303 G 511 G 305 G 525 G 307 G 555 G 313 G 571 G 317 G 573 G 319 G 577 G 333 G 604 G 347







The data and information indicated in this brochure describe conditions, requirements and examples of use for ceramic digital printing on glass. The aim is to provide the best possible information on our product TG-PRINTdigital and its opportunities in terms of application. The allocation of important information concerning the data provision and processing is an essential and central component of this manual in order to achieve the best possible printing results



Since 2009 Thiele Glas produces digital printed glass. For several years this is also possible in the maximum dimensions of up to 3210 x 18000 mm for the highest demands. Our machine manufacturer Dip-tech is one of the leading suppliers for high tech printing machinery. We currently own several Jumbo GlassJet machines for the production of large format, digitally printed glass panes. In order to stick to the latest technology, the systems are regularly adapted to new requirements and improved.

Digital printing is particularly suitable for photo

These motifs can contain dots, stripes or checks, in addition to classic photo elements. Black and white motifs, multi-colored prints, but also a combination of motif and font is possible.

In the screen printing process, a seperate screen is made for each motif. Therefore, it is especially suitable for larger quantities with the same decor. The printing can also be done with metallic shades or optionally with a non-slip decor (e.g. TG-STEP). The maximum dimensions are 2550 x 6000 mm.



Glass types:

Glass thickness:

Maximum glass dimensions:

Minimum glass dimensions:

Maximum pane weight:

Maximum printing resolution:

Printing ink:

Colors:

TG-ESG®, TG-TVG®, TG-ESG®-H

4 - 19 mm

TECHNICAL DATA TG-PRINTDIGITAL

3210 x 18000 mm (larger on request)

100 mm x 280 mm (smaller on request)

2800 kg

1440 dpi


Ceramic ink

6 basic colors freely mixable



Advantages of TG-PRINT Digital

- Printing size up to 3210 x 18000 mm (larger on request)
- Silicon bonding can be faciliated by screen printing or enameling (printing size up to 2550 x 6000 mm)
- Combinable with various Thiele Glas products (basis is always TG-ESG®, TG-ESG®-H or TG-TVG®)
- Individual color system, extensive range of colors and effects
- Finer surface compared to screen printing
- High-resolution photo-quality printing
- Appropriate for single panes and large series
- All inks are free of heavy metals
- Better printing quality
- No screens necessary



Apart from our traditional screen printing process (organic and ceramic), which limits creative possibilities, we also offer the modern digital printing on flat glass. For both, ceramic screen and digital printing, the glass is tempered after printing, the ceramic inks are melted and fired into the glass. This process gives the applied ink a long-lasting brilliance in terms of color reproduction as well as high durability and resistance to external influences. The appropriate printing method depends on your intended purpose, future application and the required colors and design.

With the digital printing process, the ink is printed directly from the printer onto the glass, which eliminated the need of screens. This offers above all time savings through shorter lead and production times and the possibility to bring elaborate photorealistic motifs onto glass. With the six basic colors, a wide range of colors from different color systems can be mixed and printed. In contrast to organic colors, where the color spectrum is limited. This is related to the components and the composition of the colors. They are also suitable for outdoor use.



BASIC COLORS



The mixture of overprinting of the basic colors can create a variety of mixed tones based on color systems such as RAL, RAL design, NCS, HKS, Pantone or Sikkens. Slight color deviations are possible. In order to check the

color brilliance and the color effect, we recommend to have a real proof sample printed before releasing the order. Please note that ceramic digital printing cannot be compared with the CMYK color system, as it is realized on paper, because it is based on different basic colors.

Printing with ceramic digital printing ink is largely scratch resistant and acid resistant according to DIN. Furthermore, light and adhesion resistance correspond to the durability of ceramic building glass melting colors.

In order to achieve desired effects like higher color saturation, it is useful to back up the digital print with a correspondending color. We recommend to use bright colors in order to influence the appearance of the digital print as slightly as possible. The thickness and opacity of the colors can be individually adapted during the printing. We distinguish between the properties normal and bonding dense.



ADVANTAGES OF CERAMIC INK

- Permanent applied on the glass
- No blistering of the ink
- Scratch and abrasion resistant, resistant to moisture
- Free of heavy metals
- Long lasting brilliance (colors are translucent and not transparent)



Most elevator glazings are very grey and dull and are hardly noticed by the viewers. That won 't happen in Aarhus, Denmark. The glazing was provided with a colorful digital print.

Due to the colorful design, the elevator exudes lightness and warmth instead of the usual cold flair



PROJECT INFORMATION

Completition:

Principal:

Executing company:

Artist:

Glass types:

Glass quantity:

Dimensions:

2016

Bygningsstyrelsen

H+ Arkitekter, Kopenhagen

Marianne Gronnow

TG-PRINTdigital on TG-PROTECT®

86 panes

up to 1300 x 2000 mm



The print motifs are often provided by our customers. Alternatively, we also offer to provide templates from the image platform stock. adobe.com. Furthermore, it is possible to choose from a variety of patterns in our Pattern Catalogue or from templates in our image database. Our pree-press department checks the usability of the data in every case.

The print motif provided by the customer should be optimized in terms of resolution as well as size and color (best possible scale 1:1, for large facades/files in consultation with us also scale 1:10). Please note, that different color rendering effects may result depending on the type of glass. In this connection especially raw material batches, ink thickness, tempering conditions and other are very important.

Upon customer request, an approval sketch and / or an image section in real resolution can be sent by email for approval of the customer before printing the motif.



FILE FORMATS AND DATA SUPPLY

Source of the print motif: provided by customer, stock.adobe.com, Pattern Catalogue,

Thiele Glas image database

File types pictures: all common graphic formats (PDF, PSD, EPS, TIFF, BMP and JPEG)

File type vector graphics: vector formats (EPS, AI, PDF)*

Fonts: except for standard fonts (Arial, Calibri, Verdana, etc.) all special


fonts have to be converted into paths, so that no substitute fonts

are integrated.

Recommended resolution:

Data supply:

from 72 dpi (highest resolution prefered – depends on motif) USB-Stick, CD/DVD, FTP upload, email (max. 10 MB), data link




LEXECAL WALLPAPER





Abstract painting

A B



Please see the image above (578 cm wide x 270 cm high - section A+B) for a better understanding of ratio and proportions.


Composition ideas:



execal

A Css Creation co.





Please see the image above (500 cm wide x 270 cm high) for a better understanding of ratio and proportions

Available colors



execal


A Css Creation co.

A B



Please see the image above 610 cm wide x 270 cm high - section A+B) for a better understanding of ratio and proportions.

Composition ideas:



A





Please see the image above (191 cm wide x 270 cm high) for a better understanding of ratio and proportions.

Available colors:



execal

A Css Creation co.



Please see the image above (620 cm wide x 300 cm high - section A+B) for a better understanding of ratio and proportions.

Available colors:










Rose Quartz

Dark Green



execal

A Css Creation co.



Please see the image above (500 cm wide x 300 cm high - section A+B+C) for a better understanding of ratio and proportions.

Available colors:



TECHNICAL DETAILS

The material we print our wallpaper on has been carefully selected to grant you a good investment. It is unwoven material of premium quality, fast and easy to hang by only pasting the wall with glue. Strong, dimensionally stable and easy to peel if it needs to be replaced. This material can be used for decorating personal spaces as well as open spaces in commercial areas. It is a premium wallpaper and very resistant to dirt. The print has vivid colors and a perfect finish.

Premium quality 350 g wallpaper | Non woven | Textured surface | UV Printed

Paste-the-wall application for easy installation | Water Resistant surface | Durable and Resistant to Damage

Destination of use: indoor, residential and contract (hotel, commercial spaces, offices)

Role width: 110 cm

At the end of the catalog you will find samples of our wallpapers. This will help you get a more accurate feeling of our products.


The samples should be considered indicative only as every wallpaper is custom-made.

Slight variations in color may occur due to limitations in the printing process.




INSTALLATION GUIDE (STEP BY STEP)

Lexecal Wallpaper is really a breeze to install, however, we recommend that you hire a professional to do it, for best results. The mural is applied to the wall with a powerful glue, with special non-woven paste. Take a look through our step by step installation guide and see how easily you can achieve your accent wall.




Make sure the wall is clean and dry




Apply a thin layer of primer




Arrange the stripes in the correct order



Mark the vertical starting point



Use an adhesive for unwoven fabrics.
Apply the glue directly to the wall



Glue the first stripe and make sure the wallpaper is right on spot



INSTALLATION GUIDE (STEP BY STEP)




Use the seam roller to get rid of bubbles



In case of leaks clear away with a moist, clean cloth



Start with the next stripe and repeat the steps until the wallpaper is complete



Trim the excess paper off with a cutter




TA-DA!
Enjoy your Accent Wall!

If you need any additional information please visit our website, accentwall.eu and check our more detailed installation guide





Fashion, function and durability make it the clear winner for your flooring choice in any room. Vibrant realistic designs and textures are combined with 100% waterproof planks and the ultimate in dent protection, providing peace-of-mind and a new-floor look for years to come.







PRYZM™ LUXURY FLOORING THE WINNING CHOICE

ELEMENTS OF HERITAGE 4.3"/5.6"/7" width planks



Vintage Multi PC020

ANTIQUED OAK 5" width planks



Natural PC003

TREELINE HICKORY 5" width planks



Amber PC006

EXOTIC WOODGRAIN



Reclaimed Gray
PC009

COASTAL CONCRETE



Seascape Gray PC010

AZURE SEA



Blue Gray

WATERFRONT

5" width planks



Sky Blue PC012

WATERFRONT

5" width planks



Pier Brown PC013

MARITIME WEATHERED



Gray PC007

VINTAGE CHESTNUT

5.7" width planks



Antique Natural **PC002**

ARTISAN FLOORBOARD

5.7" width planks




Light Brown PC004

NATIVE ACACIA

5.7" width planks



Golden PC005







ADDRESS: 52/74 STREET NUMBER - 25, ANAND PARWAT, NEW DELHI - 110005

MOBILE NO.:- +91 7220030068

EMAIL: SUPPORT@LEXECAL.COM

WEBSITE: WWW.LEXECAL.COM